



**DS-2CD732F-EPT IP Camera
Technical Manual**

Notices

The information in this documentation is subject to change without notice and does not represent any commitment on behalf of HIKVISION. HIKVISION disclaims any liability whatsoever for incorrect data that may appear in this documentation. The product(s) described in this documentation are furnished subject to a license and may only be used in accordance with the terms and conditions of such license.

Copyright © 2006-2010 by HIKVISION. All rights reserved.

This documentation is issued in strict confidence and is to be used only for the purposes for which it is supplied. It may not be reproduced in whole or in part, in any form, or by any means or be used for any other purpose without prior written consent of HIKVISION and then only on the condition that this notice is included in any such reproduction. No information as to the contents or subject matter of this documentation, or any part thereof, or arising directly or indirectly therefrom, shall be given orally or in writing or shall be communicated in any manner whatsoever to any third party being an individual, firm, or company or any employee thereof without the prior written consent of HIKVISION. Use of this product is subject to acceptance of the HIKVISION agreement required to use this product. HIKVISION reserves the right to make changes to its products as circumstances may warrant, without notice.

This documentation is provided "as-is," without warranty of any kind.

Please send any comments regarding the documentation to:
overseabusiness@hikvision.com

Find out more about HIKVISION at www.hikvision.com

Contents

1. Key Features
2. Specifications
3. Dimension

1. Key Features

- $\pm 0.1^\circ$ Preset Accuracy
- 150°/s Pan Preset Speed and 60°/s Tilt Preset Speed
- 0.7-80°/s Pan Manual Speed and 0.7-45°/s Tilt Manual Speed
- Park Action: Start to Call Preset / Patrol / Pattern / Auto Scan / Random Scan / Frame Scan, after a Defined Time of Inactivity
- Programmable Limit Stops for Auto / Random Scan / Frame Scan Modes
- Alarm I/O: 1 Channel Input and 1 Channel Relay output
- Alarm Actions: 200 Presets, 8 Patrols, 4 Patterns, Auto Scan, Alarm Output, SD Memory Recording and Notification on PC Client
- Embedded Linux OS
- TI DaVinci Hardware Compression
- H.264 video Compression
- 1 Channel Audio Compression
- Support 4CIF / DCIF / 2CIF / CIF / QCIF Real Time Compression
- Support Dual Compression Stream
- Support Motion Detection, and Notification on PC Client
- Support both Variable Bit rate and Variable Frame Rate
- Support TCP/IP, HTTP, DHCP, DNS, RTP/RTCP, PPPoE, etc.
- Support IE for Network Preview
- Support HIKVISION Watermark
- Support Network Intercom Function
- Compatible with Current HIKVISION DVR/DVS SDK and Client Software
- Built-in Surge Protection
- Working Temperature $-10^\circ\text{C} \sim 50^\circ\text{C}$ (Indoor)

2. Specifications

Parameter Model	DS-2CD732F-EPT
Camera	
Image Sensor	1/4 inch CMOS
Effective Pixels	640 (H) × 480 (V)
Lens	3.5--9mm / F1.2 / Φ14 / Auto Iris
Signal System	PAL
Day & Night	Electronic
Electronic Shutter	Auto
Min. Illumination	0.4Lux @ F1.2
S/N Ratio	More than 48dB
Video Output	1Vp-p Composite Output (75Ω/ BNC)
BLC	ON
Compression Standard	
Video Compression	H.264
Video Output	32 K ~ 2M, adjustable (8Mbps maximum)
Audio Compression	OggVorbis
Image	
Image Resolution	704 × 576, 640 × 480, 528 × 384, 704 × 288, 352 × 288, 176 × 144
Frame Rate	25fps (704 × 576)
Functions	
Horizontal Range	0 ~ 360°endless
Vertical Range	0 ~ 90°
Horizontal Speed	0.7 ~ 80°/S
Vertical Speed	0.7 ~ 45°/S
RS-485 Protocols	HIKVISION, Pelco-D, Pelco-P (addible), Self-adaptive
Pan Preset Speed	0 ~ 150°/S
Auto Mode	Auto Scan, Frame Scan, Random Scan, 8 Patrol Scan, 4 Pattern Scan.
Number of Presets	200
Auto Flip	Support
Menu Language	Chinese, English
Mouse Control	Support Mouse Drag while select HIKVISION protocol in Client Software
Dual Stream	Support
SD card Local Recording	Support
Heartbeat	Support
Password Protect	Support

Protocols	TCP / IP, HTTP, DHCP, DNS, RTP / RTCP, PPPoE (FTP, SMTP, NTP, SNMP addible).
Interface	
Audio Input	1 channel (2.0 ~ 2.4Vp-p, 1k Ω)
Audio Output	1 channel (Line level, 600 Ω)
Communication	1 RJ45 10M / 100M self-adapted Ethernet port and, 1 RS-485 interface
Alarm Input	1 channel signal input
Alarm Output	1 channel signal relay output
Others	
Working Temperature	-10 $^{\circ}$ C ~ 50 $^{\circ}$ C (Indoor)
Power Supply	12VDC, \pm 10%, (-E) series support PoE (Power over Ethernet)
Power Consumption	12W MAX
Dimensions (mm)	ϕ 145 \times 132.8
Weight	2000g

3. Dimension

